

# SLAB WOOD



**GI BETONELLA®**  
L'autentica. Dal 1979

## SPECIFICATION

Concrete paving slabs, 38 mm thick, square in shape and measuring 500 x 500 mm. The paving elements are colored using mass pigmentation with iron oxides, which is stable over time. The perimeter faces of the individual elements are all equipped with special non-through spacers 1.5 mm deep (four along all sides), which facilitate alignment during installation and ensure a self-locking effect.

The surface of the slabs is staved. The intrinsic and performance characteristics must comply with UNI EN 1339 standards. The body of the slab will be made with differentiated concrete mass, specifically: the actual body, approximately 34 mm thick in height, with concrete with an average specific weight greater than 2.20 tons/m<sup>3</sup>, which will incorporate crushed volcanic basalt aggregates with a grain size ranging from 0 to 9.5 mm; - the surface layer, with a minimum thickness of approximately 4 mm in height, with concrete with an average specific weight greater than 2.20 tons/m<sup>3</sup>, which will incorporate volcanic, crushed, and/or natural basalt aggregates with a grain size of 0 to 3 mm.



Gruppo Industriale  
**TEGOLAIA**

Gruppo Industriale TEGOLAIA  
Via della Liberazione, 48 Casier (TV) tel.

0422 671205  
fax 0422 671301

info@tegolaia.com  
www.tegolaia.com