

# TUMBLLED FENICE



**BETONELLA®**  
L'autentica. Dal 1979

## SPECIFICATION

Paving made of double-layer concrete slabs, 80 mm thick, consisting of four rectangular pieces with the following nominal dimensions: 155x155 mm, 310x155 mm, 310x310 mm, and 310x465 mm. The different-sized slabs are already assorted in packs ready for delivery and installation. The multiple sizes allow for consistent use of all the slabs.

The sharp edge of the upper face is non-rectilinear along the entire perimeter. This, combined with the 2.5 mm deep, non-through spacers on the four lateral faces, ensures a constant equidistance between slabs and continuity of the joints. This enhances the architectural effect of a stone paving made with hand-cut elements, emphasized by the fact that the surface of the individual elements is not flat but rather features raised areas and irregularly recessed areas of 3-4 mm.

The position of the spacers, interconnected with those of the adjacent slab, ensures optimal interlocking of the slabs.

The intrinsic and performance characteristics must comply with the UNI EN 1339 standard.

The blocks are subjected to a treatment that creates faulting at the edges and gives the installed flooring the appearance of a product created by hand-split edges.



Gruppo Industriale  
**TEGOLAIA**

Gruppo Industriale TEGOLAIA  
Via della Liberazione, 48 Casier (TV) tel.

0422 671205  
fax 0422 671301

info@tegolaia.com  
www.tegolaia.com